

Range: PREMIUM CARDIO

Name: PREMIUM VARIABLE STRIDE ELLIPTICAL

Product Code: ICVE2LCD

Length	2220MM	Width	716MM
Height	1760MM	Weight	220KG



Description

The Inspace Premium Adaptive Stride Elliptical Trainer delivers an impressive range to your users. 40 resistance settings and numerous programmes along with a stride adjustment of between 250mm to 1000mm ensures this product will deliver a full workout. A USB charging point and fan on this unit is as standard.

0330 110 0201 sales@inspacefitness.com | inspacefitness.com

	pace Fitness		Constant of the second s
VE-2	99		
VL-A		VE-22.1	VE-22.2
CONSOLE	DISPLAY TYPE	LED DOT-MATRIX	TFT-LCD 10.1" CAPACITIVE TOUCH SCREEN
	SAFETY KEY	-	-
	QUICK START KEY	•	•
	QUICK NUMBER KEY	•	
	DISTANCE UNIT	KM/MILE	KM/MILE
	PROGRAMS	MANUAL, GOAL, HRC ,WATT,	GOAL, HRC, RECOVERY, RPM, WATT,
		FITNESS TEST, INTERVAL, PERSET 1-3	VIRTUAL ACTIVE
DATA READOUT	DISPLAY	HEART RATE, STEP, PACE, DISTANCE, TIME, RPM, WATT, CALORIES	HEART RATE, AVG HR, MAX HR, HEART RATE ZONE, DISTANCE, TIME, STEP, WATT, CALORIES, CALORIES EFFICIENCY, METS, PACE, LEVEL, SPEED, WORKOUT PROFILE
	PRESET PROGRAM	2	
	HRC	6	5
	TEST	1	
	MANUAL	1	
	USER	14	2
	GOAL	3	3
	WATT	1	1
	RPM	-	1
	RECOVERY	-71	1
	CUSTOM	-	•
	VIRTUAL ACTIVE	-	•
PRODUCT FEATURE	MULTIMEDIA DTV IPTV WEBVIEW APP MIRROR CAST HDMI IN		 DVB-T2 OATSC-QAM (SAP PROTOCOL) 18 BOOKMARKS NETFLIX •
	FAN	•	
	BTM (BLUETOOTH MODULE)	ō	
	NFC		eGYM COMMUNICATION PROTOCOL
	QR CODE		•
	USB CHARGING	•	
	BOTTLE HOLDER	•	•
	ACCESSORY TRAY	•	•
	ERGO SEAT ADJUSTMENT	•	•
	PEDAL ADJUSTMENT	•	•
	TRANSPORTATION WHEEL	•	•
	HEART RATE RECEIVER	• 5KHz	• 5KHz 3-IN-1 (5KHz, 2.4GHz BLE, ANT+)
ECHNICAL	SOUND OUTPUT	-	 LINE OUT(3.5mm) Bluetooth Earphone Module
	RESISTENCE SYSTEM	GENERATOR	
	POWER SYSTEM	GENERATOR	
	ADAPTOR		
	RESISTENCE LEVEL	40	
	HAND PULSE	•	
	START HEIGHT	254 mm (10")	
	PEDAL (W x L)	173 x 406 mm (6.8" x 16")	
	ADAPTIVE STRIDE LENGTH	250~1000 mm	
	MINIMUM WATT VALUE	10 WATT	
	MAXIMUM WATT VALUE	400 WATT	
	MAX. USER WEIGHT	180 kgs(400 lbs)	
	WIRELESS CHEST STRAP	0	
DIMENSION	LxWxH	2220 x 716 x 1760 mm (87.3" x 28.2" x 69")	